



## OPW 126A (126A-1066 126A-1099)



The OPW 126A is recommended where surface water is a problem or wherever the fill pipe must be protected by a heavy-duty, raintight manhole. The cover and body are accurately machined to assure a leakproof seal. The 126A is typically used in conjunction with a 126B Loose Fill Cap (page 47). The cover opens and closes easily by turning 1/4 turn counter-clockwise to remove; clockwise to replace. The 126A has a 6" skirt depth.

- H2O Load Rated

### **Table of Contents:**

1. Materials
2. Ordering Specifications
3. Wrenches/Replacement Parts

## **Materials**

---

Body and Cover: cast iron

Gasket: chrome tanned leather

## Ordering Specifications

---

Product No.	in.	mm.	lbs.	kg.	
126A-1066	6"	152	15	6.7	
126A-1099	9"	224	29	13.1	

## Wrenches/Replacement Parts

---

Part No.	in.	mm.	Description
C00045M	6"	152	Wrench
126C-3099	9"	229	Wrench
H00201RS	All	Sizes	Pin
C01378I	6"	152	Cap
H00235M	6"	152	Cap Gasket
D00711I	9"	229	Cap
H00354M	9"	229	Cap Gasket
C00167I	9"	229	Locking Bar

## Wrench

---



